



PVC Strip Doors

STANDARD ~

Our standard material is produced in standard or sheet form and the strips may be either smooth or ribbed. Used in indoor and outdoor applications, the material functions best in temperatures ranging from 0 degrees to +150 degrees F.

BI-RIBBED STRIP ~

Standard and Low Temperature Gateway vinyl strip formulations are available in a unique triangular rib configuration. The softly rounded, ribbed surfaces help reduce scratching from truck and cargo traffic along with the friction and static electricity associated with smooth strips. The ribbing on both sides creates small air pockets for additional insulation and allows the strips to move apart easily as traffic passes through.

LOW TEMP ~

Low Temperature Vinyl Strip material is available in three configurations: Smooth Un-reinforced, Smooth Reinforced, or Ribbed. The material is suitable for use in freezers and in exterior applications at temperatures as low as -30 degrees F.

EXTRA LOW TEMP ~

Extra-Low Temperature Vinyl Strip material is designed for use in freezers operating in temperatures as low as -60 degrees F.

REINFORCEMENT ~

Longitudinal reinforcement for added strength and stability in certain application. The nylon cord embedded in the vinyl provides added tensile strength and reduces stretching in higher temperatures for better performance.

SAFETY STRIP ~

Gateways Safety Strips are produced in Safety Orange. These products can be used to outline hazardous area, door jambs and high traffic areas.

