



Vinyl Roll-UP High Cycle

MOUNTING OPTIONS ~

Face of Wall Mount. Stand-Off Bracket Mount.
Custom engineered according to size of opening.

Maximum 16' wide x 16' high

Doors between 40" wide and 14' high receive 2" Snaptite™ tracks with fiberglass windbars for greater durability and stability. **Head room required - 18"**.

Doors greater than 11' wide and 16' high receive 4" Snaptite™ tracks with wind stabilizer bars. Wind stabilizer bars are used for larger door openings for greater strength and durability. **Head room required - 18"**.

VINYL ~

22 ounce green vinyl solid panel with clear full width vision panel. Yellow safety stripes cover the windbars for high visibility.

EXCLUSIVE JACKSHAFT OPERATOR ~

20" per second operating speed - 100+ cycles per day, ½ hp, 115 volt, 1 phase, 8 amps

Electronic memory control board wired to accept most activations, has built-in automatic timer to close. Manual chain fall operation in case of power loss.

3 position push button station (open, close, stop)

OPTIONAL ACTIVATIONS ~

Watertight Motor, Splash Proof Cover, 460 volt - 3 Phase Motor, Safety Edge, Radio Controls, Pull Cords, Photo Eyes

RESET SYSTEM ~

Interlocking brush seal is incorporated at the top of the Snaptite™ tracks causing a reset system. Should the door be forced out of the tracks by accidental impact, the door is designed to reset back into the guides.

WEATHERSTRIPPING ~

Grey vinyl weatherstripping is angled to provide a tighter seal preventing bugs and insects easy access or entry.

Aluminum Bottom Profile Bar with cushioned edge and a bottom draft seal for positive floor contact. **Breakaway Feature** is used in the bottom profile bar to help prevent damage to the door by accidental impact.



Vision Panel Not Shown