

Roll-Up Doors: Header & Wall Mount Survey

1) INFORMATION	
A. Company:	C. Quote #
B. Job Name:	D. Door Name:
2) DIMENSIONS	
	tions or issues that may hinder installation. ents should be in inches.
1	
HEAD ROOM	
	NATURAL DESIGNATION OF THE PROPERTY OF THE PRO
	WIDTH
SIDE	SIDE
CLEARANCE	CLEARANCE
	WIDTH
3) DOOR MATERIAL	6) OPERATION STYLE
☐ Bug Barrier®	Manual Spring-Loaded
22 oz. Vinyl	Manual Chain Hoist
☐ 40 oz. Vinyl	Automatic In-Tube Motor Internal 120V 52 RPM Motor
4) DOOR COLOR:	High Cycle External Jackshaft Operator Requires 18" of head room and 18" of side room.
Standard stock colors are Green, Blue, Black, and Yellow. A variety of other colors are available upon request.	Single Phase: ☐120V / ☐ 240V
	Three Phase: ☐ 208V / ☐ 480V / ☐ 600V ☐ Water-tight (Nema-4)
5) MOUNT STYLE Doors use 8" of head room and 5" to 13" total of side room depending	□ vvater-tigrit (Nerria-4)
on track width.	7) OPERATION DRIVE SIDE: ☐Right / ☐ Left
Header Mount / In Jamb All doors manufactured with +/- 1/8" tolerance.	As viewed from mounting surface.
☐ Wall Mount / Face of Wall	8) WIND STABILIZER
☐ Interior / ☐ Exterior	Standard Windbar. Pocket Color:
	Aluminum Hinges for higher windloads.